

# ***Interactive comment on “Sea Level Variability in the Swedish Exclusive Economic Zone and adjacent seawaters: Influence on a Point Absorbing Wave Energy Converter” by Valeria Castellucci and Erland Strömstedt***

## **Anonymous Referee #1**

Received and published: 28 May 2019

The article “Sea Level Variability in the Swedish Exclusive Economic Zone and adjacent seawaters: Influence on a Point Absorbing Wave Energy Converter” investigates sea level variability in the Baltic Sea to be used for the identification of a location to deploy wave energy converter (WEC) systems. This study is of great interest for WEC developers, however, before I can recommend publication, I recommend a major revision.

Major comments:

[Printer-friendly version](#)

[Discussion paper](#)



The main result of this study is shown in Figure 10b, defining the optimal sites for the deployment of WECs when only considering MSL variability. However, as written by the authors on page 15, line 5-6, this might change when considering for example the full sea states at each side. As the motivation of this paper is to provide a tool for WEC developers for choosing deployment sides, who need to take not only the MSL variability into account, I would like to suggest to extend Figure 10, showing also a figure on how the regions of optimal deployment side would change when not only MSL variability is considered.

Regarding sea-ice, on page 14, line 1-2 it is stated that the ice-concentrations have to be considered, but in this study it is only computed for ice-free conditions as all ice-variables are assumed to be zero (page 5, line 1). In addition, on page 13, line 2-6 (result section) was written an overview about ice-concentration and wave power summarized from other studies. May one could move this paragraph to the introduction and than include an argumentation why ice can be neglected in this study in the method section near page 5, line 1. And what happens with the WEC when sea-ice exists?

Page 14, line 28-32 and page 15 line 17-18: How are the other WECs systems, mentioned in the introduction, are influenced by MSL variations compared to the Uppsala WEC?

Please include equations to the manuscript for the calculations performed in this study. Although the calculations are not too complex, it would be much easier to grasp what has been calculated (and from which data) from the additional equations than only from text.

In addition, a time period from 2007-2016 was chosen, which includes a strong barotropic salt water inflow event in December 2014 (driven by a strong sea level gradient between the Baltic Sea and the Kattegat). What influence has this event on the MSL variability and the WEC systems? What about other short term variability? Please also discuss this or why it is neglected. The chosen time period from 2007-2016 rep-

[Printer-friendly version](#)[Discussion paper](#)

resents the current situation. How are possible future changes included in this tool, as this is also needed for the decision making process of the WEC developers?

#### Minor comments

 Figure 1: This figure is very similar to the figure in Castellucci et al. (2016). Therefore, please include something like “adapted from ... ” in the figure caption as reference.

 Page 2, line 22: “to give an example, let us consider...” → The Uppsala WEC system is considered as example.

 Page 4, line 13 - page 5, line 12: Unfortunately, the paragraph is not clear to me. Are the simulations done within this study or are they performed by SMHI in another study? Is the MSL extracted from NAMOD with a 44 km grid resolution or is it the one available at marine.copernicus.eu? Or is the second one used for validation? Is the 44 km grid resolution not a bit coarse for studies in the Baltic Sea? Is the validation of the model results part of this or a different study? etc. Please rewrite this section to clarify what simulations performed and what data has been used within this study. Please also acknowledge all work or data provided from others (if this is the case) with references and mention them in the acknowledgment section.

 Page 5, line 2: Please include the reference for the atmospheric forcing (HIRLAM data set)

 Page 5, line 3: Modeled MSL is normally strongly affected by data assimilation. Therefore it would be very beneficial to have a short overview on which variables are assimilated and which are affected and how, before referring to the studies describing the assimilation process in detail.

 Page 5, line 12: Why are extreme events are neglected in this study. What impacts have extreme events on WECs?

 Page 5, line 26: Is the MSL range computed from the hourly data?

Printer-friendly version

Discussion paper



Page 6, line 15: semester → time period

Page 8, line 9: When you computed the pooled standard deviation, did you include a weighting. If yes, please specify it.

Figure 3 and 4: Please use the same color scale to be able to compare the figures.

Figure 5 and 6: Please use the same color scale to be able to compare the figures.

Page 10, line 8-11 and Figure 7: please clarify if this is from Castellucci et al. (2016) or results of this study. Please include light gray grid lines for easier identification of the  $\pm 0.8\text{m}$  MSL.

Page 12, line 8: “It is interesting to filter out areas with low enough MSL ...”, Did you mean that you wanted to “filter out” regions with higher MSL variations and keep the areas with low enough MSL variations, here? Or did I misunderstood something?

Page 16, line 4: “are available on-line”, please add where to find them

Please discuss the possibility of using this study to find deployment location in other regions as the Baltic Sea in the discussion section

References: please include the DOIs for all the references

Interactive comment on Ocean Sci. Discuss., <https://doi.org/10.5194/os-2019-39>, 2019.

Printer-friendly version

Discussion paper



# Sea Level Variability in the Swedish Exclusive Economic Zone and adjacent seawaters: Influence on a Point Absorbing Wave Energy Converter

Valeria Castellucci<sup>1</sup> and Erland Strömstedt<sup>1</sup>

5 <sup>1</sup> Div. of Electricity, Dept. of Engineering Sciences, Ångström Laboratory, Uppsala University, Box 534, 75121, Uppsala, Sweden

*Correspondence to:* Valeria Castellucci (valeria.castellucci@angstrom.uu.se)

**Abstract.** Low-frequency sea level variability can be a critical factor for several wave energy converter (WEC) systems, for instance linear systems with a limited stroke length. Consequently, when investigating suitable areas for deployment of those WEC systems, sea level variability should be taken into account. In order to facilitate wave energy developers in finding the most suitable areas for wave energy park installations, this paper describes a study that gives them additional information by exploring the annual and monthly variability of the sea level in the Baltic Sea and adjacent seawaters, with focus on the Swedish Exclusive Economic Zone. Over 10 years of reanalysis data from the Copernicus project have been used to conduct this investigation. The results are presented by means of maps showing the maximum range and the standard deviation of the sea level with a horizontal spatial resolution of about 1 km. A case study illustrates how the results can be used by the WEC developers to limit the energy absorption loss of their devices due to sea level variation. Depending on the WEC technology one wants to examine, the results lead to different conclusions. For the Uppsala point absorber L12 and the sea state considered in the case study, the most suitable sites where to deploy WEC parks from a sea level variation viewpoint are found in the Gotland Basins and in the Bothnian Sea, where the energy loss due to mean level variations is negligible.

## 20 Nomenclature

$H_s$	Significant wave height
MSL	Mean sea level
MSSHR	Maximum sea surface height range
$MSSHR_y$	Annual maximum sea surface height range based on $SSH_{1h}$
$MSSHR_{10y}$	Decadal maximum sea surface height range based on $SSH_{1h}$
$MSSHR_{m,10y}$	Monthly maximum sea surface height range for each month averaged over 10 years, based on $SSH_{1h}$
SD	Standard deviation
$SD_y$	Annual standard deviation of $SSH_{1h}$
$SD_{10y}$	Decadal standard deviation of $SSH_{1h}$
$SD_{m,10y}$	Monthly standard deviation of $SSH_{1h}$ for each month, pooled over 10 years


SDR <sub>10y</sub>	Standard deviation of the MSSHR <sub>y</sub> over 10 years
SEEZ	Swedish Exclusive Economic Zone
SL	Sea level
SMHI	Swedish Meteorological and Hydrological Institute
SSH	Sea surface height
SSH <sub>1h</sub>	Sea surface height with hourly resolution
SWERM	Swedish wave energy resource mapping
T <sub>e</sub>	Energy period

## 1 Introduction


In the Baltic Sea, the variations of sea level (SL) are controlled by meteorological and climatological processes, including the hydrological balance (Johansson et al., 2001). Tides give a small contribution to these variations, since the Scandinavian basins are characterized by low tidal levels during the year. As suggested by (Ekman, 2009), the Baltic Sea has no real tides, but storm winds could raise the sea level locally by more than 2.4 m. The largest amplitudes reach up to 3 – 4 m as storm surges and seiches in the Gulf of Finland (Kulikov et al., 2014). In general, the tide is a few centimeters high, with peaks of about 24 cm in the Gulf of Finland, as estimated by (Medvedev et al., 2016). In (Samuelsson and Stigebrandt, 1996) the sea level variations are classified as ‘external’ and ‘internal’: respectively, long-term winds transporting water between the Atlantic Ocean and the Baltic Sea, and short-term winds together with changes of density and barometric pressure, redistributing water within the Baltic Sea. Those two types of variability may exhaustively explain the low-frequency SL changes in the Baltic Sea. Being that those changes are predominantly influenced by air pressure and wind stress, the variability is mostly of random character and seasonal cycles are dominant (Kulikov et al., 2014). According to Hünike et al. (2005) during the summer, temperature and precipitation explain part of the SL variability except in the Kattegat region. Furthermore, SL exhibits an annual cycle peaking in the winter months.

SL variations are of great importance and have been thoroughly investigated by many researchers for example with the purpose of broadening the knowledge on climate change (IPCC, 2018), spatial patterns (Ekman, 1996) (Donner et al., 2012), land uplift (Miettinen et al., 1999), and the pole tide (Ekman, 1996) (Medvedev et al., 2014) in the Baltic Sea. The reason why the study presented in this paper has been carried out is to give wave energy developers additional information to use when looking for suitable sites for their devices. Generically, a wave energy converter (WEC) extracts energy from high-frequency waves, while it might be negatively affected by low-frequency SL changes depending on its design. The Uppsala WEC, shown in Fig. 1, is considered as an example. The WEC consists of a surface-floating buoy vertically driving an encapsulated linear generator on top of foundation acting as a fixed reference on the sea floor. The tension in the connection line and the distance between the buoy and the sea bed is influenced by low-frequency sea variations: for a significantly low SL, the connection line is slack and the translator rests on the bottom of the generator; while for a significantly high SL, the translator continuously hits the upper end-stop, which results in additional stresses on the hull of the generator and in a reduced stroke of the translator itself. In both

cases, the energy absorption decreases drastically, together with the lifetime and survivability of the WEC (Castellucci et al., 2016). The same problem is experienced by other technologies, such as oscillating water columns, as suggested in Muetze and Vining (2006) and Lopez et al. (2015), and in more general terms by WECs which have a part that is fixed in position relative to the seabed and a part that moves with the waves. Well-known point absorbers, such as Carnegie CETO (Kenny, 2014),  
5 Ocean Power Technologies Powerbuoy (OPT, 2018), and Archimedes Wave Swing (Beirdol et al., 2007) are challenged by SL changes, either because of a limited stroke length or because of the exponential decrease in available energy with depth. The work presented in this paper is part of a bigger wave energy project on Swedish wave energy resource mapping (SWERM) financed by the Swedish Energy Agency (Strömstedt et al., 2017). The project aims to generate and combine different layers of information, like bathymetry, sea ice coverage, wave climate, wave energy conversion potential, etc., for the Swedish  
10 Exclusive Economic Zone (SEEZ) in order to identify the most suitable areas for wave energy conversion. Within this framework, the study here conducted aims to evaluate the SL information layer: the paper presents the results for the SL variations over a larger area, that includes the SEEZ and adjacent seawaters (see Fig. 2). The input data and the methodology are discussed in Chapter 2. The results shown in Chapter 3 by means of maps, which will be available on-line or on request, so that detailed data can be extracted. Finally, discussion and conclusion are presented in Chapters 4 and 5.  
15



**Figure 1: Illustration of the point absorber WEC developed at Uppsala University. Reprinted from Castellucci et al. (2016).**



**Figure 2: Left) Map of the SEEZ around Sweden in focus for this study. Right) Map of the considered water basins. The same basin terminology is used throughout the article. Credits to HELCOM (2018).**

## 5 2 Data and methods

In order to produce comprehensive maps of sea surface height (SSH) in the Baltic Sea as a whole, it is necessary to interpolate the available data over space and time. However, measurement stations are located far from each other, even more than 100 km, and some are visited only once a month. Some may lack observations for very long time periods. In order to compensate for those deficiencies, observations are combined with model simulations to obtain a homogeneous data set with high resolution in time and space, and reasonably close to observations. This can be achieved with a process called data assimilation, in which observations are used to update the circulation model to keep it from deviating too far away from reality (Axell and Liu, 2016).

The circulation model used by the Swedish Meteorological and Hydrological Institute (SMHI) to produce the reanalysis data used in this study is HIROMB (High-Resolution Operational Model for the Baltic). HIROMB has open boundaries in the western English Channel and in the northern North Sea. For SSH, HIROMB uses data from the coarse storm-surge model NOAMOD (44 km resolution), whereas climatological monthly mean values are used for salinity and temperature. Moreover, ice variables are assumed to be zero at the boundary. The meteorological forcing is from the High-Resolution Limited Area

Model (HIRLAM, 2019), with a resolution of 22 to 11 km. The chosen data assimilation method is the 3DEnVar (3-D Ensemble Variational) data assimilation, a multivariate method where many variables are affected by each observation. The observations assimilated into this model are ice concentration, level ice thickness, sea surface temperature, and profiles of salinity and temperature. The directly affected model variables are the same, i.e. ice concentration, level ice thickness, salinity and temperature. Other variables are affected indirectly to a small degree, including e.g. currents and SSH (through its effects on density). However, the differences compared to a free run without data assimilation is rather small. For more information regarding the model description and validation see (Axell and Liu, 2016) and the product documentation (Copernicus, 2018). In general, the results obtained for SSH in the SEEZ and the adjacent seawaters are rather good: mean correlations of about 0.91 and mean RMS errors of about 9 cm are calculated by comparing hourly instantaneous model data with corresponding coastal observations for three different years. The SSH data available on-line at *marine.copernicus.eu* have a spatial resolution of 1/20 degrees in the north-south direction and 1/12 degrees in the east-west direction, which translates into about 5.5 km resolution. The requirement set by the SWERM project is to work on a common grid of about 1 km<sup>2</sup>, hence, the reanalysis data have been linearly interpolated with the purpose of fitting this grid. Moreover, a 10-year data set (2007 to 2016) with a temporal resolution of one hour has been chosen in order to examine the annual and monthly variability of the SSH<sub>1h</sub> oscillations, neglecting extreme events.

The metrics considered relevant to this study are the maximum range and the standard deviation of the sea level variations. Note that both metrics are independent of the choice of reference level. The range, calculated as the highest SSH<sub>1h</sub> and lowest SSH<sub>1h</sub> during the selected time period, gives an indication of the maximum variation of SL. Some WEC technologies may be unaffected by variations below a certain range, like the Uppsala WEC in mild wave climates, as discussed in Chapter 4. Furthermore, the highest absorption loss for a device can be estimated by WEC developers as presented in the case study in Chapter 3, and mitigation measures can be adopted. The standard deviation (SD), calculated as the square root of the variance for the chosen data set, quantifies the dispersion of the data from their mean value. The higher the SD, the more spread out the data points are from the expected value, hence, it is a measure of the variability of the SL variations. When selecting a site for WEC deployment, one may find it preferable to choose an area with as constant conditions as possible: the frequency of occurrence of high ranges is greater for higher values of SD and the design costs for a WEC may increase with it. In general, the lower the standard deviation, the better it is. Moreover, both metrics, range and SD, are independent of the choice of reference level, which for sea level is not always self-evident (Johansson et al., 2001). In fact, the data set provided by Copernicus have a zero mean value at the outer boundary, in the Atlantic. In the Baltic Sea, the SL is higher due to the density difference between the Atlantic Ocean and the Baltic Sea.

The SL range is calculated in Eq. (1) and (2) as the difference between the absolute maximum and minimum values over the 10-year data set of SSH<sub>1h</sub>, MSSHR<sub>10y</sub>, and over 10 years per each month, MSSHR<sub>m,10y</sub>. In other words:

$$MSSHR_{10y} = \max(SSH_{1h,i}) - \min(SSH_{1h,i}) \quad (1)$$

$$MSSH_{m,10y} = \max(SSH_{1h,m|10y}) - \min(SSH_{1h,m|10y}) \quad (2)$$

where  $i = 1, 2, \dots, N$  with  $N$  being all the  $SSH_{1h}$  in the 10-year data set, and  $m$  corresponds to the month of the year.

The SD has been obtained, using Eqs. (3) – (6), as the average of annual SDs over the 10-year data set,  $SD_{10y}$ , and as the square root of the pooled variance to aggregate monthly SD over 10 years,  $SD_{m,10y}$ . More specifically:

$$SD_{10y} = \sum_{y=1}^{10} \frac{SD_y}{10} \quad (3)$$

$$SD_y = \sqrt{\frac{1}{n_y - 1} \sum_{ii=1}^n [SSH_{1h,ii} - \overline{SSH_{1h,ii}}]^2} \quad (4)$$

$$SD_{m,10y} = \sqrt{\sum_{y=1}^{10} \frac{SD_y^2}{10}} \quad (5)$$

$$SD_y = \sqrt{\frac{\sum_1^{12} (n_m - 1) SD_m^2}{\sum_1^{12} (n_m - 1)}} \quad (6)$$

where  $ii = 1, 2, \dots, n_y$  with  $n_y$  equal to 365 or 366, depending on the year, while  $n_m$  is the number of days for each specific month. The pooled variance in Eq. (6) is weighted taking into consideration that every month has a different number of days. Finally, a case study is presented in order to give an idea of how the results can be used by wave energy developers. The Uppsala WEC technology is considered. In particular the energy absorption of an L12 generator is simulated by hydrodynamic modeling. The following features are assumed: a cylindrical buoy of radius 3 m and draft 0.6 m; a translator stroke length of about 2.5 m; a total weight of the moving parts except the buoy of 10 tonnes; a damping factor of about 135 kNs/m. For more details regarding the model and its limitations see (Castellucci et al., 2016). For the mere purpose of providing an example of WEC energy absorption at different SLs, a sea state characterized by a significant wave height  $H_s = 1$  m and energy period  $T_e = 5$  s is used as input to the model. These values are considered to be a reasonable approximation of the wave climate in the Baltic Sea (Soomere et al., 2007) (Soomere et al., 2011) (I. Zaitseva, 2013).


### 15 3 Results

The results for SL range and SD are summarized in Sect. 3.1.1 and 3.1.2 respectively. The energy absorption as a function of the SL for an Uppsala WEC is estimated for a specific sea state and presented in Sect. 3.2.


## 3.1 Sea level metrics

### 3.1.1 Range

The MSSHR variations during the years 2007 to 2016 has been calculated from the interpolated reanalysis data sets. Fig. 3 shows the highest monthly ranges over the 10-year period ( $MSSHR_{m,10y}$ ) in the Scandinavian basins. Fig. 4 shows, on the left, the average of the annual maximum ranges ( $MSSHR_y$ ) and, on the right, the absolute maximum range over 10 years ( $MSSHR_{10y}$ ). The variability of  $MSSHR_y$ , estimated as the standard deviation of the  $MSSHR_y$  over 10 years ( $SDR_{10y}$ ), has a minimum value of 0.05 m between the Danish islands and the coast of Germany and a maximum of 0.5 m in the innermost part of the Gulf of Finland. In general, a quite moderate variation ( $SDR_{10y} < 0.3$  m) is calculated along the Swedish coast. The time period from April to September (summer-time) appears to be the one with the lowest ranges compared to the period October to March (winter-time) as shown in Fig. 3. The spatial pattern is clear and almost independent of the time of the year: the greatest oscillations of  $MSSHR_{m,10y}$  occur in the Bothnian Bay, the Gulf of Finland, the Kattegat and in the Danish straits. The legend in Fig. 3 is capped at 2 m to better illustrate the variations inside the SEEZ, but the SL can actually reach 4 m in the eastern parts of the Finnish gulf. The Northwestern Gotland Basin is the most stable area, characterized by  $MSSHR_{10y}$  ranges of 1.2 to 1.5 m (see Fig. 4). However, during summer-time the range is likely to be lower than 0.7 m.



**Figure 3: MSSHR<sub>m,10y</sub> (Monthly maximum ranges [m] for each month over 10 years, 2007-2016, of re-analysis data). The red areas illustrate MSSHRs higher than about 1.8 m, up to 4 m.**



**Figure 4: Left) Average MSSHR<sub>y</sub> (average annual maximum ranges over the 10-year window). Right) MSSHR<sub>10y</sub> (decadal maximum ranges over the 10-year window). The color scale is different from the one in Fig. 3 for ease of readability and visualization.**

### 5 3.1.2 Standard deviation

The standard deviation (SD) of the SSH<sub>1h</sub> has been evaluated in order to have a better understanding of the variability of the data set. The SD of the SSH<sub>1h</sub> has been calculated for each month and, then, aggregated by month over the 10-year windows by computing a pooled SD ( $SD_{m,10y}$ ). The results are shown in Fig. 5. Afterwards, the monthly SDs have been pooled over each year to obtain the annual pooled SDs. The average of those 10 annual SDs,  $SD_{10y}$ , is shown in Fig 6.

- 10 With reference to Fig. 5, the spatial and temporal patterns are once again clear. In the Gotland Basins the pooled  $SD_{m,10y}$  is the lowest, especially in the summer-time when the  $SD_{m,10y}$  values can be as low as 0.05 m (May). The  $SD_{m,10y}$  increases as we move out from the center of the Baltic Sea and a peak of 0.4 m is calculated in the Skagerrak, by the northern coast of Denmark, during the month of January. In the same area, the  $SD_{10y}$  is found to be 0.32 m, while the lowest  $SD_{10y}$ , about 0.08 m, is found in the Northwestern Gotland Basin (see Fig. 6). As expected, the variability of the data determined as the average of annual
- 15 SD,  $SD_{10y}$ , turns out to have a smaller interval than the pooled monthly SD ( $SD_{m,10y}$ ) used to aggregate monthly SDs over 10 years.





Figure 5:  $SD_{m,10y}$  (Monthly SD [m] for each month over 10 years, 2007-2016, of re-analysis data).



**Figure 6:  $SD_{10y}$  (SD of the MSSHR, over the 10-year window). The color scale is different from the one in Fig. 5 for ease of readability and visualization.**

### 3.2 Case study

5 In Castellucci et al. (2016) the hydro-mechanic model that analyses the behaviour of a point absorber is described. In particular, the model evaluates how sea level variations influence the power absorption, hence the energy production, of the Uppsala WEC across a representative scatter of wave climates. Note that power is absorbed as long as the translator moves within the stator (see Fig. 1). An example is presented in Fig. 7 with the purpose of pointing out the effect of mean sea level (MSL) changes on the performance of the Uppsala WEC denoted L12 (Castellucci et al., 2016). Let's assume that the hypothetical

10 wave energy developer is interested to deploy a wave energy park where the significant wave height is not greater than 1 m. The normalized annual energy absorption for MSL in the range  $\pm 0.8$  m is close to 100 % and it drops drastically for  $|MSL| > 0.8$  m, as illustrated in Fig. 7. When the MSL exceeds the stroke length of the translator, i.e. 2.5 m, then the WEC is not capable of absorbing any power. In fact, when the  $MSL > 2.5$  m, the translator is stuck on the upper part of the generator hull and the buoy is submerged; on the contrary, when  $MSL < -2.5$  m, the translator is resting on the lower end stop and the

15 connection line to the buoy is slack.




Figure 7: Normalized annual energy absorption as a function of the MSL for a L12 Uppsala WEC and for a sea state characterized by  $H_s = 1$  m and  $T_e = 5$  s. The markers indicate the results of the hydro-mechanic simulations, while the solid line serves as a guide to the eye. Adapted from Castellucci et al. (2016).





Figure 8: Lowest minima (left) and highest maxima (right) of MSL during the period 2007 to 2016, after subtracting the mean value.


The validity of the results presented in Fig. 7 are limited to a specific sea state ( $H_s = 1$  m,  $T_e = 5$  s) and mostly dependent on the significant wave height, rather than the energy period (Castellucci et al., 2016). In particular, the plateau shown in Fig. 7 becomes wider with decreasing values of  $H_s$ . As a consequence, the energy absorption of WECs deployed in the patches of sea characterized by  $H_s \leq 1$  m will be unaffected in the MSL range of  $\pm 0.8$  m at least. For the technology here considered, the MSSHR<sub>10y</sub> should be complemented with the minimum and maximum values of SL: the WEC is not affected if the highest maximum and the lowest minimum do not exceed  $\pm 0.8$  m at the desired site. The highest maxima and lowest minima in the studied area are shown in Fig. 8. For the purpose of the SWERM project, aiming at screening for suitable sites for wave energy utilization in the SEEZ, it is interesting to highlight areas with low enough SL variations to allow 100 % normalized annual wave energy absorption, as described by the case study and Fig. 7, with a typical wave climate for the SEEZ possibly interesting enough for energy conversion purposes. For this reason, we have generated a map of  $H_s$  for ice-free conditions within the SEEZ, illustrated in Fig. 9. Ice-free conditions are more interesting for wave energy conversion purposes. These simulations completely separate, but using the same geographical grid network and spatial resolution.



**Figure 9. Ice free average significant wave height,  $H_s$ , in the SEEZ from a 16 year high-resolution hindcast from the SWERM-project with methods described in (Strömstedt et al., 2017) and (Nilsson et al., 2019).**

$H_s$  has been estimated within the SWERM-project (Strömstedt et al., 2017), and methods for modelling are described in Nilsson et al. (2019). In the wave climate modelling ice concentration below 30 % is considered ice-free. Above 30 % ice concentration, the sea is modelled as flat surface and energy is assumed to be completely attenuated by the ice (Tuomi et al., 2011). The percentage of time with ice concentration above 30 %, based on 35 years of ice data from 1980 to 2014, is mapped and presented in (Strömstedt et al., 2017). The difference in annual mean wave power estimates for ice-free conditions and ice-time-included statistics is mapped and presented by Nilsson et al. (2019).

For the purpose of illustrating the most interesting areas with regard to low MSL variations and low negative impact on wave energy absorption the  $MSSHR_{10y}$  presented in Fig. 4, is masked using the results in Fig. 8 and 9 as filters. The process of masking the range of SL with limiting values of maximum ( $\leq +0.8$  m), minimum ( $\geq -0.8$  m) and  $H_s$  ( $\leq 1$  m) results in the left image of Fig. 10, which highlights the areas where the WEC energy absorption is unaffected by the changes in MSL, i.e. part of the Northwestern and Eastern Gotland Basins, and a small area in the Bothnian Sea. The right image in Fig. 10 highlights areas where  $H_s = 0.9 - 1.1$  m, corresponding with the  $H_s$  that applies to the function in Fig. 7, and where the variations of the MSL are less than  $\pm 0.8$  m and thus low enough to always allow a normalized energy absorption of 100 % based on a statistical confidence interval of 95 % defined by two standard deviations ( $2SD_{10y} < 0.8$  m). A hypothetical WEC developer that is willing to pick a site where to deploy a park of Uppsala WECs may be interested to select one of the aforementioned basins with regard to sea level variations.



20 **Figure 10: Left) Maximum range ( $MSSHR_{10y}$ ) masked with the limiting values  $\pm 0.8$  m and significant wave height ( $\leq 1$  m). The blue line indicates the boundary of the SEEZ. Right) The areas where  $H_s$  is 0.9 – 1.1 m and where a normalized energy absorption with regard to MSL is 100 % according to Fig. 7 with a confidence interval of 95%.**

## 4 Discussion

When designing WECs and choosing suitable sites for wave parks deployment one generally has to consider wave power potential, water depth and seabed profile, distance to shore, accessibility and permissions, ice-concentration, SL variations, etc., which are all studied in the SWERM project for the SEEZ. This paper gives an overview of the SL variations in the SEEZ and adjacent seawaters by means of the maps presented in Chapter 3. The same methodology described in Chapter 2 can be used to produce SL information layers for other regions than the Baltic Sea.

As discussed among others by Johansson et al. (2001), Ekman (1996) and Stramska et al. (2013) the variability at a specific location of the Baltic Sea shows no apparent trend on a short time scale (10 days to 3 months), while it does on a seasonal time scale, when significantly higher variations in winter- compared to summer-time are observed. Moreover, they argue that the spatial behaviour of the SD is clear on both interannual and seasonal time scales and it follows a specific pattern. These findings are in strong agreement with the results presented in this paper (see Fig. 5 and 6).

The highest decadal ranges presented in Fig. 4 show that the range of oscillations increases as we move out from the Northwestern Gotland Basin (Min value = 1.2 m) to the Bothnian Bay, the Danish straits and the Gulf of Finland (Max value = 4.3 m). The monthly ranges shown in Fig. 3 confirm the same spatial pattern and a not surprising seasonal tendency: the range is lower during summer-time and higher during winter-time, in particular, July is the mildest month and January the one with the highest ranges.

The SD of the  $SSH_{1h}$  confirms the same spatial and temporal patterns. Based on the  $SD_{m,10y}$  (see Fig. 5), the most pronounced variability appears to occur during the winter-time (Nov-Jan), while the summer-time (May-Jul) is the one with the smallest variability. In general, the values of SD are quite large if compared with the rest of the globe (see (Ducet et al., 2000) Plate 1 and (Thompson et al., 2016) Fig. 3), meaning that the variability of the  $SSH_{1h}$  is rather big. With reference to Fig. 6, the lowest  $SD_{10y}$  values are found in the Bothnian Sea, Åland and Archipelago Sea, Gotland Basins, characterized by  $SD_{10y} \leq 0.1$  m.

Note that a gap in the  $SSH_{1h}$  data set has been identified during few days in February 2008 and from the 24/2 to the 10/3 of 2012. This does not influence the results in a drastic way considering that February and March are not the most critical months and that the missing data points are a small percentage ( $\sim 0.5$  %) of the total analysed data set. Regarding the peaks of  $SSH_{1h}$  that are important when calculating the maximum ranges, the reanalysis model of SMHI tends to underestimate them. However, the correlation between model and observations is 0.91, and the RMS error is 9 cm for the Baltic Sea (Copernicus, 2018). An educated guess by SMHI would be that the underestimation is about 10 %. In general, the model responds correctly to changes in air pressure, winds, tides, and so on.

As mentioned before, low-frequency changes in SL may affect the performance of WECs. The case study presented in this paper aims to give an idea of the magnitude of the problem and to provide an example for WEC developers. A specific point absorber, the Uppsala WEC, and a representative annual average significant wave height ( $H_s$ ) of 1 m are here considered. The first assumption limits the validity of the results for other devices: the energy absorption as a function of the SL variation (Fig. 7) should be carefully simulated or measured case by case. The second assumption reduces the scatter diagram of the sea state

occurrences to one average state at an unspecified site: a WEC developer should select the most suitable sites on the basis of e.g. the accessibility and the wave power resource, then calculate the energy output for different sea states and aggregate the results in order to narrow down the number of suitable sites.

For the examined case, the areas where the WEC energy absorption is unaffected by the changes in SL are part of the Gotland Basins and a limited area of the Bothnian Sea, where the  $MSSHR_{10y}$  is contained in the interval [1.15 - 1.55] m (see Fig. 10).  
5 If a more detailed analysis would be carried out, considering e.g. the full scatter diagram of sea states at each site, then the basins highlighted in Fig. 10 would certainly be different. Moreover, solutions for mitigating the negative effect of SL variations may be considered, e.g. the stroke length of the Uppsala WEC could be extended by applying changes in the design of the generator, or a compensation system to regulate the length of the connection line could be included in the design of the  
10 converter (Castellucci et al., 2016). Integrating a solution into the WEC design would increase the number of sites for wave park deployment, but most likely at higher capital investment cost.

Finally, it should be mentioned that according to the wave power technology one wants to investigate, a more detailed analysis of the frequency of occurrence of high ranges at a chosen site could be useful. This choice is dictated by the requirements set by every specific wave energy technology.

15

## 5 Conclusions

The dependency of the energy absorption on the low-frequency SL variation for wave energy converters is a matter of interest for different WEC technologies. For this reason, the changes in SL in the SEEZ and adjacent seawaters have been investigated  
20 in the frame of the SWERM project. The study carried out in this paper aims to give a deeper understanding of the variability of the SL in those basins and to provide an information layer that, once the SWARM project will be completed, will be combined with other layers of information to suggest suitable sites for wave park deployment.

From the calculation of the  $SSH_{1h}$  standard deviation, it is clear that the variation of the high-frequency oscillations during the latest decade are limited especially in the Bothnian Sea, Åland and Archipelago Sea, Gotland Basins, where  $SD_{10y} \leq 0.1$  m.  
25 The maximum range of these variations increases as we move out from the Northwestern Gotland Basin to the Bothnian Bay, the Danish straits and the Gulf of Finland. The  $MSSHR_{10y}$  varies from the lowest value of 1.2 m (Northwestern Gotland Basin) to the maximum value of 4.3 (Gulf of Finland) during the period 2007-2016. The seasonal variability is evident: it is more pronounced during the winter-time and less during the summer-time. The spatial variability is also noticeable and almost independent of the month: the highest oscillations are found in the Bothnian Bay, the Gulf of Finland, the Kattegat and in the  
30 Danish straits, reaching up to 4 m in the Gulf of Finland. More constant conditions are found in the Northwestern Gotland Basin, characterized by  $MSSHR_{10y}$  of 1.2 to 1.5 m, with very low range during summer-time ( $< 0.7$  m).

With the purpose of comprehending how the SL can affect a point absorber WEC, an example has been shown. An Uppsala WEC with specified features has been considered and the energy absorption as a function of the MSL has been evaluated, assuming a wave climate of relevance for wave energy conversion with a high rate of occurrence in the SEEZ and adjacent seawaters. From a MSSHR<sub>10y</sub>-point-of-view, areas suitable for deployment are found in the Bothnian Sea, Northwestern and Eastern Gotland Basins, where the 10-year maximum range is contained in the interval [1.15 – 1.55] m.

The data sets here displayed by means of geographic maps will be available on-line or on request by the end of the SWERM project, and can be used by WEC developers to perform analysis according to the technology and models they work with. Moreover, the data will be used to complete the SWERM project that intends to merge different layers of ocean data for the SEEZ. Further information about the project will be available on the following homepage in the fall 2020:  
10 <http://www.teknik.uu.se/electricity/research-areas/wave-power/>.

### Acknowledgments

The authors would like to thank The Swedish Energy Agency for funding the project (Project no. 42256-1) within the national Swedish research program for marine energy conversion. The project is also supported by the Swedish STandUP for Energy research alliance, a collaboration initiative financed by the Swedish government. StandUP for Energy is acknowledged for providing a research infrastructure. The authors would like to thank the Swedish Meteorological and Hydrological Institute (SMHI) for the geological input data on sea level variations from the Copernicus project and, in particular, Dr. Lars Axell for valuable input on the simulations performed by SMHI. The authors would also like to thank Dr. Erik Nilsson at the Department of Earth Sciences, Uppsala University, for the average ice-free significant wave height data in Fig. 9.

20

### References

- Axell, L. and Liu, Y.: Application of 3-D ensemble variational data assimilation to a Baltic Sea reanalysis 1989-2013, *Tellus A*, 68, 24220, 2016. DOI: 10.3402/tellusa.v68.24220
- Beirdol, P., Valério, D., and Costa, J. S. D.: Linear model identification of the Archimedes Wave Swing, In Proceedings of the International Conference on Power Engineering, Energy and Electrical Drives, Setubal, Portugal, 12–14 April 2007. DOI: 10.1109/POWERENG.2007.4380214
- Castellucci, V., Eriksson, M., and Waters, R.: Impact of Tidal Level Variations on Wave Energy Absorption at Wave Hub, *Energies* 9(10), 843, 2016. DOI: 10.3390/en9100843
- Copernicus, Marine environment monitoring service. Product documentation: <http://cmems-resources.cls.fr/documents/QUID/CMEMS-BAL-QUID-003-008.pdf>, last access: 18 April 2018.

30

- Donner, R. V., Ehrcke, R., Barbosa, S. M., Wagner, J., Donges, J. F., and Kurths, J.: Spatial patterns of linear and nonparametric long-term trends in Baltic sea-level variability, *Nonlin. Processes Geophys.*, 19, 95-111, 2012. DOI: 10.5194/npg-19-95-2012
- Ducet, N., Le Traon, P. Y., and Reverdin, G.: Global high-resolution mapping of ocean circulation from TOPEX/Poseidon and ERS-1 and -2, *J. Geophys. Res.*, 105(C8), 19, 477–19, 498, 2000. DOI: 10.1029/2000JC900063
- Ekman, M.: A Common Pattern for Interannual and Periodical Sea Level Variations in the Baltic Sea and Adjacent Waters, *Geophysica*, 32(3), 261-272, 1996.
- Ekman, M.: The Changing Level of the Baltic Sea during 300 Years: A Clue to Understanding the Earth, Summer Institute for Historical Geophysics, Åland Islands, 2009. ISBN: 9789529252411
- 10 HELCOM: <http://www.helcom.fi/>, last access: 14 May 2018.
- HIRLAM: <http://hirlam.org/index.php/hirlam-programme-53/welcome-to-hirlam>, last access: 20 June 2019.
- Hünike, B., and Zorita, E.: Influence of temperature and precipitation on decadal Baltic Sea level variations in the 20th century, *Tellus A*, 58(1), 2005. DOI: 10.1111/j.1600-0870.2006.00157.x
- IPCC Assessment report. Available on line: [https://www.ipcc.ch/pdf/assessment-](https://www.ipcc.ch/pdf/assessment-report/ar5/wg1/WG1AR5_Chapter13_FINAL.pdf)
- 15 [report/ar5/wg1/WG1AR5\\_Chapter13\\_FINAL.pdf](https://www.ipcc.ch/pdf/assessment-report/ar5/wg1/WG1AR5_Chapter13_FINAL.pdf) , last access: 15 May 2018.
- Johansson, M., Boman, H., Kahma, K. K., and Launiainen, J.: Trends in sea level variability in the Baltic Sea, *Boreal Environment Research*, 6:157-179, 2001.
- Kenny, S.: Carnegie Wave Energy, Internship Report, Murdoch University. Perth, Australia, 2014.
- Kulikov, E. A., Medvedev, I. P., and Koltermann, K. P.: Baltic sea level low-frequency variability, *Tellus A*, 67:1, 2014. DOI:
- 20 10.3402/tellusa.v67.25642
- López, I., Pereiras, B., Castro, F., and Iglesias, G.: Performance of OWC wave energy converters: Influence of turbine damping and tidal variability, *Int. J. Energy Res.*, 39, 472–483, 2015. DOI: 10.1002/er.3239
- Medvedev, I. P., Rabinovich, A. B., and Kulikov, E. A.: Pole Tide in the Baltic Sea, *Oceanology*, 54(2), 121-131, 2014. DOI: 10.1134/S0001437014020179
- 25 Medvedev, I. P., Rabinovich, A. B., and Kulikov, E. A.: Tides in Three Enclosed Basins: The Baltic, Black, and Caspian Seas, *Frontiers in Marine Science*, 3:46, 2016. DOI: doi.org/10.3389/fmars.2016.00046
- Miettinen, A., Eronen, M., and Hyvarinen, H.: Land uplift and relative sea-level changes in the Loviisa area, southeastern Finland, during the last 8000 years, Department of Geology, University of Helsinki. *Positiva* 99-28, 1999.
- Muetze, A., and Vining, G. J.: Ocean wave energy conversion—A survey, In *Proceedings of the IEEE Industry Applications Conference*, Tampa, FL, USA, 8–12, October 2006. DOI: 10.1109/IAS.2006.256715
- 30 Nilsson, E., Rutgeresson, A., Dingwell, A., Björkqvist, J.-V., Pettersson, H., Axell, L., Nyberg, J., and Strömstedt, E.: Characterization of Wave Energy Potential for the Baltic Sea with Focus on the Swedish Exclusive Economic Zone, *Energies*, 12, 793, 2019. DOI: 10.3390/en12050793

- Ocean Power Technologies (OPT): <http://www.oceanpowertechnologies.com>, last access: 18 April 2018.
- Samuelsson, M., and Stigebrandt, A.: Main characteristics of the long-term sea level variability in the Baltic sea, *Tellus A*, 48:5, 1996. DOI: 10.3402/tellusa.v48i5.12165
- 5 Soomere, T., and Zaitseva, I.: Estimates of wave climate in the northern Baltic Proper derived from visual wave observations at Vilsandi, 48 *Proc. Estonian Acad. Sci. Eng.*, 13, 1, 48–64, 2007.
- Soomere, T., Weisse, R., and Behrens, A.: Wave climate in the Arkona Basin, the Baltic Sea, *Ocean Sci.*, 8, 287–300, 2012. DOI: 10.5194/os-8-287-2012
- Stramska, M., Kowalewska-Kalkowska, H., and Świrgoń, M.: Seasonal variability in the Baltic Sea level, *Oceanologia*. 55(4), 2013, 787-807, 2013. DOI: 10.5697/oc.55-4.787
- 10 Strömstedt, E., Haikonen, K., Engström, J., Eriksson, M., Götteman, M., Sundberg, J., Nyberg, J., Zillén-Snowball, L., Nilsson, E., Dingwell, A., and Rutgersson, A.: On Defining Wave Energy Pilot Sites in Swedish Seawaters, In *Proceedings of the 12th European Wave and Tidal Energy Conference (EWTEC)*, 27 August – 1 September 2017, Cork, Ireland.
- Thompson, K. R., and Demiro, E.: Skewness of sea level variability of the world's oceans, *Journal of Geophysical Research, Oceans*. 111, C05005, 2016. DOI: 10.1029/2004JC002839
- 15 Tuomi, L., Kahma, K., Pettersson, H.: Wave hindcast statistics in the seasonally ice-covered Baltic Sea, *Boreal Environ. Res.*, 16, 451–472, 2011.
- Zaitseva, I.: *Wave Climate and its Decadal Changes in the Baltic Sea Derived from Visual Observations*, Doctoral thesis, Tallin University of Technology, 2013.